



Congratulations!

You have just purchased one of the finest Recessed Screens ever made. Constructed of the finest materials available & the finest Craftsmanship, your Guarantee of quality will be evident through out the years of beauty & enjoyment you will receive from this Screen.

### **INSTALATION INSTRUCTIONS – RECESSED SCREENS**

1. Do not remove the protective paper covering from the Header Bar until installation is complete.
2. Hold the header bar in place so that the face of the bar is flush with the Fireplace opening & the slotted Mounting Brackets rest against the Lintel Bar, which is the steel angle bar in the roof of your fireplace.
3. Locate hole position for self-tapping screws (enclosed in a small plastic bag) by marking inside the slots of the Mounting Brackets.
4. Using 11/64” drill bit, make the necessary holes, one for each Mounting Bracket slot is sufficient.
5. Insert a self-tapping screw in each hole and screw in. This will cut thread in the hold you just drilled. Then remove the screws.
6. Place the Header Bar face down on a **soft, clean** surface & slip the Curtain Rod off Support Arms at each end. Remove the Sleeve Clip from each end of the Curtain Rod.
7. Slide the Mesh Curtain onto the Curtain Rods, starting with the side that is minus the Ring. In case of a Corner Screen, the long panel of Curtain goes around the corner.(See #10 for Manual Screen)
8. Replace the Sleeve Clip on the end of the Curtain Rods with the long protruding strip facing away from the center of the Curtain Rods. The last ring in the Curtain Mesh should now be placed on the end of the Clip & the long protruding strip should be knuckled over to hold the last ring in position at the end of the Curtain Rod. Replace Curtain Rod on the Supporting Arms (from where they were removed).
9. TRAVERSE PULL (end pull operation): Spread the rings, which are connected to the Pull Chain, & connect each to the first spiral of Mesh just over the bent part of the Stiffener Rod.

10. MANUAL PULL (center pull operation): One side of each curtain has 3 rings spaced closely together. This portion of Curtain Mesh goes in the center of the Curtain Rod Insert Curtain Rod through the 3' close together' rings, and then slide on the Spring. After the sleeve, place the Ring which is attached to the Pull onto the Curtain rod and continue sliding the remainder of the Curtain Rings on.
11. Hold the assembled Screen in position in the Fireplace and using the washers furnished with the screws, fasten the Screen to the Lintel Bar. Remove the protective paper covering. Reach under the Bar and with a screwdriver: slide the Sleeve Clip with the ring knuckled on against the sidewall of the fireplace so that the stiffener rod hugs the sidewall.

SIDE WALL MOUNTING – G-94: Hold the Facia Bar Assembly into the Fireplace, making sure the Facia Bar is straight and mark on the side wall of the Fireplace where the holes are to be drilled (2 on each side). Use 5/16" masonry drill bit for the proper fit of the screws and lead shields included with the Screen.

BOTTOM GUARD – F-92: Do not remove protective paper from the face of the Bar until installation is completed. Place Bottom Guard into position in Fireplace, making sure the Bar is straight & mark the floor of the Fireplace where holes are to be drilled (one hole for each bracket is sufficient). Use 5/16" masonry drill bit for the proper fit of screws and lead shields included with the Screen.

### **MAINTENANCE AND CLEANING INSTRUCTIONS**

The Curtain Rod is dry lubricated for easy operation. For continued ease in opening and closing rub a small amount of Powdered Graphite (available at your local Hardware Store) along the top of the Curtain Rod. This should be done several times annually.

The surfaces of this Screen (Header Bar, Bottom Guard, Pulls etc.) are made tarnish resistant with a hard protective coating. **DO NOT POLISH – DO NOT USE ABRASIVE CLEANERS.** A soft (facial tissue is best), dry or damp (depending on the condition) cloth will safely remove dust and soil.

Do not allow hot ashes or coals to gather around Bottom Guard, the direct heat from these will mark the finish.

Always remember that for the proper operation of your Fireplace the damper should be **ALL THE WAY OPEN!**

**GUARENTEE:** *Stone Manufacturing's* Custom Recessed Curtain Screens are guaranteed for one full year from date of receipt against any defects in mechanism or material when operated under normal conditions.

Now sit back & enjoy the warm glow of a fireplace fire with the feeling of security that you will receive from this Custom Recessed Curtain Screen made especially for you by Stone Manufacturing.